

JEDI 2.0
Solaris 9
Public Design
Review
30 October 2003



- **Solaris 9 Public Design Review**

- ➡ – JEDI 2.0 Requirements
 - Support for Solaris 9
 - Transition JEDI Tools to Role Based Access Control
 - Transition JEDI Tools to Solaris Management Console
 - Removing Dependency on JEDI Maps
 - Secure Shell
 - JASS Interface
 - Pluggable Authentication Modules
 - Flash Archive Support
 - Optional SASF for Solaris 9
 - Integration of ISS into JEDI 2.0 Baseline
 - Additional Recommendations

- **Support for Solaris 9**

- JEDI shall
 - Be reengineered to run in the Solaris 9 Operating Environment
- The Operating Environment shall
 - Be hardened
 - Have a secure file system
 - Use the fix-modes software
 - Use the Solaris fingerprint database
 - Minimize the number of installed accounts
 - Lock unused accounts
 - Start only required services
 - Minimize the required services
 - Minimize the footprint of the system
 - Secure the Solaris Kernel
 - Restrict NFS Server Requests
 - Prevent attempts to execute code on stacks
 - Restrict access to core files

- **Transition JEDI tools to Solaris Management Console (SMC)**
 - SMC tools shall
 - Be extended
 - Operate within the SMC framework
 - Conform to the SMC look and feel
 - Have no dependencies
 - Have an associated 16 bit icon
 - Have an associated 32 bit icon
 - Conform to the Sun package standard
 - Conform to existing auditing requirements
 - Support the Graphical SMC Interface
 - Not destroy system data input through other programs

- **Transition JEDI tools to Native Role Based Access Control (RBAC)**
- **Remove dependency on JEDI Maps**
 - The JEDI software shall
 - Remove the dependency on the existing JEDI Maps functionality
 - Update operating system files and tables directly
 - Retain the capability to backup and restore name service data

- **Integrate Internet Security System's (ISS) Security Scanner**
 - The Security Scanner shall
 - Be included with the JEDI distribution
 - Be installed separately from JEDI
 - Use ISS Installation Scripts
 - Security risks and vulnerabilities shall be documented in the System Security Authorization Agreement (SSAA)
 - Templates shall be documented in the SSAA
 - SPI-NET shall be removed from the JEDI baseline

- **Secure Shell**

- JEDI shall

- Support secure shell and secure commands
 - Provide a configuration GUI to run the ssh-keygen command
 - Support secure shell on Solaris 8

- **Incorporate new native Pluggable Authentication Modules (PAM)**

- JEDI shall

- Incorporate the Solaris 9 native PAM

- **Flash Archive Support**
- **Optional Segmented Application Support Framework (SASF) for Solaris 9**
 - JEDI shall
 - Allow for the optional installation of the Segmented Application Support Framework (the DII COE)
 - Provide a version of the DII COE that will run on Solaris 9
 - Use the current version of DII COE and the current patch
 - Support installation of the Integrated C4I System Framework (ICSF) Segments on Solaris 9

- **Point and Click Installation**

- JEDI shall

- Provide a graphical user interface for installation
 - Provide a consistent look and feel
 - Provide consistent interfaces for Setup, Administration, and DNS
 - Shall support NIS, NIS+, LDAP, and local file installations
 - Shall support Jumpstart Installations


- **Solaris 9 Supported Naming Services**
 - JEDI shall support
 - NIS+
 - NIS
 - LDAP/Sun ONE
 - Local Files
 - An upgrade path from JEDI v1.3 on Solaris 8

- **Solaris 9 Public Design Review**

- JEDI 2.0 Requirements
- ➡ – Support for Solaris 9
- Transition JEDI Tools to Role Based Access Control
- Transition JEDI Tools to Solaris Management Console
- Removing Dependency on JEDI Maps
- Secure Shell
- JASS Interface
- Pluggable Authentication Modules
- Flash Archive Support
- Optional SASF for Solaris 9
- Integration of ISS into JEDI 2.0 Baseline
- Additional Recommendations

- **Support for Solaris 9**
 - Solaris 9 - Security Architecture
 - Solaris 9 - Security in the Solaris OE
 - Solaris 9 - Solaris Installation Security
 - Solaris 9 - JEDI PreInstallation
 - Solaris 9 - JEDI PostInstallation
 - Solaris 9 - JEDI User Environment
 - Solaris 9 - JEDI/Solaris OE Security

Solaris 9 - Security Architecture



- **Security will be pervasive in the JEDI Installation**
 - Solaris Installation
 - JEDI PreInstallation
 - JEDI Installation
 - JEDI PostInstallation

- **Software installed as part of Solaris Installation**
 - Minimized Solaris OE Packages
 - User Cluster will be the base
 - Individual Components will be identified and documented in the ICG
 - Solaris Management Console (SMC) Components
 - Dynamic Host Configuration Protocol (DHCP)
 - Secure Shell
 - Jumpstart Architecture and Security Scripts (JASS) Toolkit
 - Fix-modes Software
 - Solaris Fingerprint Database

Solaris 9 - Solaris Installation Security

SUNWmccom - SMC Common Components
SUNWmcc - SMC Client Components
SUNWmc - SMC Server Components
SUNWwbmc - SMC WBEM Components
SUNWmgapp - WBEM Management Applications
SUNWmga - Solaris Management Applications
SUNWdcInt - Solaris Diskless Client Management Applications
SUNWpmgr - Solaris Patch Management Applications
SUNWrmi - Resource Management User Interface Components
SUNWlvmr - Solaris Volume Management (root)
SUNWlvma - Solaris Volume Management APIs
SUNWlvmg - Solaris Volume Management Applications

- **Minimizing Solaris Management Console Components**

- Individual Components will be identified and documented in the ICG

**Shared
Libraries**

**System
Support**

Solaris APIs

Java Virtual Machine (JVM)

Shared Libraries

Linux Libraries

Common Files and System Code

Scheduler & Res. Mgmt

Directory

TCP

VFS

NFS

IP

Volume Management

Virtual Memory

Device Driver

Device Driver

Device Driver

Device Driver

Device Driver

Platform Specific Code

Processor Specific Code

Solaris Kernel

- **Solaris Architecture after Solaris Installation**
 - Modular
 - Highly Configurable
 - Supports multiple architectures

JEDI FOR SOLARIS 9

Release Notes ►
Installation & Configuration Guide (ICG) ►
User Manual (UM) ►

INSTALL JEDI ►►



Joint Enterprise DoDHS Infrastructure



Version Description
Document (VDD)

Site Security
Authorization Agreement (SSAA)

Master Security Requirements
Traceability Matrix (SRTM)

Software & Security Test
Description (SSTD)

Trusted Facility
Manual (TFM)

Training Management
Plan (TMP)

AFRL Consolidated Help Desk
jdhs.help@af.mil
Comm: (315) 330-1DHS (4347)
DSN: 597-1DHS (4347)

OR Northrop Grumman IT Help Desk
Comm: (402) 291-8300

JEDI Program Mgmt. Office
jedi@af.mil
AFRL/IFE B
32 Brooks Road, Rome, NY 13441
Comm: (315) 330-7657
DSN: 597-7657
Fax: (315) 330-7107

Unclass: <https://extranet.it.afil.af.mil/jedi>
Sipnet: jedi@af.mil
Intalink: <http://web1.rome.mil/jedi>

These files require Adobe Acrobat to view. [INSTALL](#) Acrobat Reader 5.0 now.



NORTHROP GRUMMAN
Information Technology



JEDI 2.0 Installation



Installation Directory

Please select the directory where you would like JEDI installed. Include the full path.


Install Directory:

Required Free Space: 512000 KB
Available Space: 750000 KB

JEDI



JEDI 2.0 Installation

 Solaris Automated Configuration

The auto-configuration program provides an intuitive interface that will allow you to install and configure JEDI based on customized choices. In addition, the auto-configuration program will allow you to examine your configuration settings before any actual configuration is applied. For additional assistance on selecting the installation method, refer to the Installation and Configuration Guide (ICG) provided on the JEDI CD-ROM.

Do you wish to run Auto-Configuration now?
☒ Yes ☐ No

This auto-configuration file is generated by the auto-configuration program and is used to auto-load various configuration settings. If this is the first time the auto-configuration program is being executed, an auto-configuration file will not exist on this workstation. An auto-configuration file may be imported from other JEDI systems to this system to accelerate the configuration process.

Do you have an existing Pre-JEDI configuration file prepared?
☐ Yes ☒ No

Location of existing configuration file:

JEDI

JEDI 2.0 Installation



Security Configuration


The current EEPROM security-mode is: none
Do you want to change the security-mode?
☒ Yes ☐ No

Choose the security-mode: ☐ command ☐ full ☒ none

The current non-console root login setting in the "/etc/default/login" file is: null
Do you wish to allow non-console root logins?
☒ Yes ☐ No

JEDI

Review Help < Back Next > Cancel



JEDI 2.0 Installation

Configure Audit Control

Do you wish to initialize the audit control configuration with the default JEDI settings or the existing system settings?

☒ **Default JEDI**
☐ **Existing system**
☐ **None**

Enter full path of default audit directory location:

Browse...

Enter full paths to overflow audit directories:

Browse...

Minimum free space: %

Configure flags

Configure naflags

flags=

no <input type="checkbox"/>	fr <input checked="" type="checkbox"/>	fw <input checked="" type="checkbox"/>	fa <input type="checkbox"/>	fm <input checked="" type="checkbox"/>
fc <input type="checkbox"/>	fd <input checked="" type="checkbox"/>	cl <input type="checkbox"/>	pc <input type="checkbox"/>	nt <input type="checkbox"/>
ip <input type="checkbox"/>	na <input type="checkbox"/>	ad <input checked="" type="checkbox"/>	lo <input checked="" type="checkbox"/>	ap <input checked="" type="checkbox"/>
io <input type="checkbox"/>	ex <input type="checkbox"/>	ot <input type="checkbox"/>	all <input type="checkbox"/>	

JEDI

Review


Help

< Back

Next >

Cancel

JEDI 2.0 Installation

 **Name Service Configuration**

Name Service Type:
NIS

Workstation Type:
Master

☐ **Import Existing Tables**
☒ From tar file
☐ From tape archive


Default Router:
192.168.1.1

Domain Name:
mydomain

Table Location:
/var/yp/src Browse...

JEDI

Review Help < Back Next > Cancel



JEDI 2.0 Installation

 LDAP Configuration

Full Machine Name: myhost.mydomain.ldap

Server Root Directory: /usr/netscape/server4

Administrative Domain: mydomain.ldap

Administrative ID: admin

Config Directory URL: ldap://myhost.mydomain.ldap:389/

User Directory URL: ldap://myhost.mydomain.ldap:389/dc=mydomain,

Server Port: 389 Administrative Port: 4000

Server Identifier: myhost

Suffix: dc=mydomain,dc=ldap

Root DN: cn=Directory Manager

Server IP Address: 192.168.1.11 Run As: root

Use Replication: ☐ Yes ☒ No

Supplier Initiated: ☐ Yes ☒ No

Replica (Consumer) Host Name:

JEDI

Review Help < Back Next > Cancel

JEDI 2.0 Installation

 JEDI

Home Directory Configuration

Home Directory Server: ☒ **Server** ☐ **Client**

Mounting Type: ☐ **Static** ☒ **Auto**

Mount Point:

Servers:

Home Dir Clients:

Please enter any Home Directory clients and servers. (One per line)

JEDI

JEDI 2.0 Installation



Mail Hub Configuration

Mail Hub: ☒ Server ☐ Client


Mail Hub Clients:

Enter the name of mail clients to this host (One per line)

JEDI

Review Help < Back Next > Cancel

JEDI 2.0 Installation



Mail Hub Configuration

Mail Hub: ☐ Server ☒ Client

Mail Hub Hostname:

Mail Hub IP Address:

JEDI

Review Help < Back Next > Cancel

JEDI 2.0 Installation



Mail Aliases Configuration

Enter the destination addresses for the following Aliases:

root:	<input type="text" value="ciso@mailhost"/>
isso:	<input type="text" value="ciso@mailhost"/>
admin:	<input type="text" value="cadmin@mailhost"/>
oper:	<input type="text" value="coper@mailhost"/>
audit_wam:	<input type="text" value="isso@mailhost"/>

JEDI

JEDI 2.0 Installation

 JEDI


TCP Wrappers

Services: Host List (Comma Separated):

Services	Hosts
----------	-------

JEDI

JEDI 2.0 Installation



Network Printer Configuration

Printer Name:

Printer IP Address:

Printer Alias:

Printer Device:

/dev/null

Add / Modify

Delete

Name	Alias	IP Address	Device
------	-------	------------	--------

JEDI

Review

Help

< Back

Next >


Cancel

JEDI V2.0

33







- **Administration, Setup, and DNS installation GUIs will be reengineered in Java**
- **Underlying support scripts will support Jumpstart Installations**

JEDI V2.0 Administration - User Account Administration

User Account Administration

User Account

☒ Own Choice ☐ cisso ☐ cadmin ☐ coper

User Information

User Name:

Full Name:

Description:

User ID Number:

Password:

Verify Password:

Primary Group:

Home Directory Server:

Home Directory Path:

Mail Server:

Mailhost:

Alias:

Login Directory:

Shell:

Account Information

Type: ☐ System ☒ Network Information Service (NIS)

NIS Makefile Path:

Create User Account Now?

Navigation icons: Back, Forward, Home, Stop, Refresh, Print, Search, Help

• User Account Administration

- Creates user accounts on the system
 - Fields mirror data collected for SMC
 - Add User Wizard
- Default fields will be set for SMC including Primary Project

JEDI V2.0 Administration - Role Administration

Role Administration

User Account

☒ Own Choice
 ☐ isso
 ☐ dadmin
 ☐ oper

User Information

Role Name:
 Full Name:
 Description:
 Role ID Number:
 Role Shell:
 Role Password:
 Confirm Password:
 Home Directory Server:
 Home Directory:
 Members (space separated list):

Account Information

Type:
 ☐ System
 ☒ Network Information Service (NIS)

NIS Makefile Path:

Create User Account Now?

Navigation icons: Back, Forward, Home, Stop, Refresh, Print, Help

- **Role Administration**
 - Creates roles on the system
 - Fields mirror data collected for SMC
 - Role Creation Wizard
 - Default fields will be set for SMC including Primary Project

• Assign Privilege

– Assign Rights to chosen roles

- Reads
/etc/security/prof_attr
- Updates
/etc/user_attr



- **Network Port**

- Sets port for CLASS
- Sets Makefile path

JEDI V2.0 Administration - Network Port


Network Port

CLASS Server
Aliases: class_s class_server
Port (tcp): 222

CLASS Client
Aliases: class_c class_client
Port (tcp): 222

Account Information
Type: ☐ System ☒ Network Information Service (NIS)
NIS Makefile Path: /var/yp/Makefile
Alter Network Ports Now? Yes

Navigation icons: Back, Forward, Home, Stop, Refresh, Print, Help



• Enable/Disable Network Ports

- Displays contents of services file
- Services recommended for disabling are displayed at the top of the scrollable list
- Updates the JASS_SVCS_DISABLE variable in the JASS configuration file
 - On subsequent runs of JASS, the specified services will be disabled

• Recommended Services to disable


Kshell	Discard	submissiona
New-rwho	sysstat	rje
Rmonitor	daytime	finger
Monitor	chargen	x400
Pcserver	time	X400-smb
Sun-dr	name	Csnet-ns
Kerberos	whois	Uucp-path
Krb5-pop	bootps	nntp
Cvc	bootpc	netbios
www-ldap	hostnames	slp
Klogin	pop2	Mobile-ip
Snmp (client)	pop3	Cvc-hostid
Echo	Imap	Courier
uucp	Biff	talk
	rping	

- **Disable/Lock Accounts**
 - Displays contents of passwd file
 - Accounts recommended for locking or disabling are displayed at the top of the scrollable list
 - Updates the JASS_ACCT_DISABLE and JASS_ACCT_REMOVE variables in the JASS configuration file
 - On subsequent runs of JASS, the specified users will be disabled




• Disable/Lock Groups

- Reads the contents of the group file
- Groups recommended for disable/lock are displayed at the top



Solaris 9 – JEDI PostInstallation

- **Accounts recommended for disabling**
 - SA
 - COE
 - Keyman
 - SSO
 - Secman
 - Sysadmin
- **Accounts recommended for locking**
 - Uucp
 - Nuucp
 - Nobody
 - Listen
- **Groups recommended for locking**
 - Uucp
 - Nuucp





- **Enable/Disable Start Up Processes**

- Displays a list of processes recommended for disabling

- Sets the uppercase first letter in the startup script name to lower case

- Script will not be executed






- **Remove Development Software**
 - Removes development packages from the system

• Environment

– Environment Settings for


- Window Manager
- Temp directory
- Time Zone
- Web Browser
- Open Windows Home Directory






- **X Environment**
 - Environment Settings for
 - Login Header
 - Login Greeting
 - Colors
 - Lockout Configuration
 - Frame Buffer
 - X Server Options


- **Network Services**
 - Network Time Protocol Settings



- **CLASS**
 - Settings for CLASS client and server



- **DNS Resolver**
 - Configures workstation as a DNS client





• Print Banners

- Optional removal of JEDI Print Tool
- Optional suppression of Banner Pages and Classification Labels
- Sets Branch, Organization, and Location for Print Banner

The screenshot shows a Windows-style window titled "JEDI V2.0 SECURITY - PRINT BANNERS". The window has a header bar with the JEDI logo and the text "Print Banners". Below the header, there are three main sections: "Configuration", "Information", and a "Execute Print Banner Changes Now" button. The "Configuration" section contains four rows of radio button options: "Remove the Print Facility?" (Yes/No), "Suppress Banner Pages?" (Yes/No), "Suppress Classification Label Pages?" (Yes/No), and "Default Print Mode" (Command Line/Graphical User Interface (GUI)). The "Information" section contains three text input fields labeled "Service Branch", "Organization", and "Location". At the bottom of the window, there is a row of five buttons: a blue arrow pointing left, a printer icon, a printer icon, a printer icon, and a "HELP" button.

- **Security Labels**

- Sets Classifications, Codeword, Caveats, and Handling Instructions for Printed Output
- Not used for Trusted Solaris

The screenshot shows the 'JEDI V2.0 SECURITY - SECURITY LABELS' window. It features a header with the JEDI logo and a title bar. Below the header, there are five radio buttons: 'Classifications', 'SI Codewords', 'TK Codewords', 'Caveats', and 'Handling Instructions'. The 'Classifications' radio button is selected. Below these buttons is a large empty text area. Underneath the text area, there are two buttons: 'Add Classification' and 'Remove Selected Classifications'. Below these buttons, there are two text input fields: 'System High Label' and 'System High Short Label'. Below the 'System High Label' field, there is a question: '"For Demonstration Purposes Only" on All Print Banners?' with two radio buttons: 'Yes' and 'No'. Below the 'System High Short Label' field, there is a text input field labeled 'Security Labels' and an 'Import...' button. At the bottom of the window, there is a button labeled 'Execute Security Labels Changes Now' with a lightning bolt icon. The bottom of the window has a navigation bar with five buttons: a back arrow, a printer icon, a document icon, a printer icon, and a 'HELP' button.



- **Security Banner**
 - Sets what to display on Banner
 - Configures Security Banner
 - Not used for Trusted Solaris



- **Required Server Fields Configuration**
 - Sets DNS domain and networks

The screenshot shows a window titled "JEDI V2.0 DNS Administration - Required Server Fields Configuration". The window has a logo on the left and a title bar. Below the title bar, there is a section titled "Required Server Fields Configuration". The configuration fields are as follows:

Field	Value
Server Type	<input type="radio"/> Primary <input type="radio"/> Secondary <input type="radio"/> None
DNS Domain	spock.dns
IP Address of Networks (space separated list)	137.51.155, 137.51.154
Named Directory	/etc/namedb

At the bottom of the window, there is a row of seven buttons: a back arrow, a globe, a globe with a grid, a globe with a grid, a globe with a grid, a globe with a grid, and a "HELP" button.




The screenshot shows the 'JEDI V2.0 DNS Administration - Advanced Server Fields' window. The title bar includes the JEDI logo and the text 'JEDI V2.0 DNS Administration - Advanced Server Fields'. The main title is 'Advanced Server Fields Configuration'. The window contains several configuration fields and options:

- Administrator Mail Address: Postmaster
- Host File: /opt/jedi/etc/named/hosts
- Name Servers: tstne2-spock
- Mail Server: mailhost
- Name Server Hints File: db.cache
- Suppress non-Mail Server MX Records? ☒ Yes ☐ No
- Use MX Domain Records: ☐ Yes ☒ No
- Named Boot File: named.boot
- Named Boot File Directory: /etc
- Keep Authorization for Other Domains? ☐ Yes ☒ No
- Start of Authority (SOA) Times (in minutes):
 - Refresh: []
 - Retry: []
 - Expire: []
 - Time To Live: []

At the bottom, there is a row of icons: a back arrow, a globe, a server rack, a server rack with a plus sign, a server rack with a minus sign, a globe, and a 'HELP' button.

- **Advanced Server Fields Configuration**
 - Sets advanced DNS Configuration settings

- **Cache Hints**
 - Sets the location of Cache hints




- **Secondary Server Fields**

- Sets type of DNS server

The screenshot shows a window titled "JEDI V2.0 DNS Administration - Secondary Server Fields". The window has a header bar with the JEDI logo on the left and the text "Secondary Server Fields Configuration" on the right. Below the header, there is a section for "Server Type" with two radio buttons: "Primary" and "Secondary". The "Secondary" radio button is selected. Below this, there is a text field for "Primary Server IP Address". Further down, there are two more radio button groups: "Maintain copies of the Data Base Files?" with "Yes" and "No" options, and "Cache Only?" with "Yes" and "No" options. At the bottom of the window, there is a row of seven buttons: a back arrow, a globe icon, a globe icon with a grid, a globe icon with a grid and a cross, a globe icon with a grid and a cross, a globe icon, and a "HELP" button.

- **DNS Resolver Configuration**
 - Sets DNS Domain
 - Sets IP Address of Primary and Secondary Servers

The screenshot shows the 'JEDI V2.0 DNS ADMINISTRATION - DNS RESOLVER' window. It features a title bar with standard window controls. Below the title bar is a logo for 'Joint Enterprise DoD/US Infrastructure JEDI'. The main area is titled 'DNS Resolver Configuration'. It contains three radio buttons for 'Type': 'Client' (selected), 'Server', and 'None'. Below these are four text input fields: 'DNS Domain' (containing 'spock.dns'), 'IP Address of Primary Name Server', 'IP Address of Secondary Name Server (Optional)', and 'IP Address of Secondary Name Server (Optional)'. At the bottom right of the main area is an 'Import...' button. The bottom of the window has a row of seven icons: a back arrow, a globe, a globe with a grid, a server rack, a server rack with a globe, a globe, and a 'HELP' button.



- **Fix-modes**


- Corrects modes on files
- Executed during PostInstallation

- **Fingerprint Database**


- Validates base Sun provided files
- Installed during PostInstallation

- **During PostInstallation, JEDI 2.0 will**
 - Restrict NFS Server Requests to a privileged system port
 - /etc/system
 - Set nfssrv:nfs_portmon = 1
 - Prevent attempts to execute code on stacks
 - Restrict the ability to overwrite parts of the program stack of a privileged program
 - /etc/system
 - Set noexec_user_stack = 1
 - Set noexec_user_stack_log = 1
 - Use *coreadm* to
 - Store core files in /var/core
 - Generate a syslog message when a core file is created

- **After PostInstallation, all Security Components are in place and configured**



Solaris 9 - JEDI User Environment



Solaris 9 - JEDI User Environment

Console

Console

Read Only Console

JEDI V2.0 Login (gto)
NOTICE AND CONSENT LOG-ON BANNER.

THIS IS A DEPARTMENT OF DEFENSE COMPUTER SYSTEM. THIS COMPUTER SYSTEM, INCLUDING ALL RELATED EQUIPMENT, NETWORKS AND NETWORK DEVICES (SPECIFICALLY INCLUDING INTERNET ACCESS), ARE PROVIDED ONLY FOR AUTHORIZED U.S. GOVERNMENT USE. DOD COMPUTER SYSTEMS MAY BE MONITORED FOR ALL LAWFUL PURPOSES, INCLUDING TO ENSURE THAT THEIR USE IS AUTHORIZED, FOR MANAGEMENT OF THE SYSTEM, TO FACILITATE PROTECTION AGAINST UNAUTHORIZED ACCESS, AND TO VERIFY SECURITY PROCEDURES, SURVIVABILITY, AND OPERATIONAL SECURITY. MONITORING INCLUDES ACTIVE ATTACKS BY AUTHORIZED DOD ENTITIES TO TEST OR VERIFY THE SECURITY OF THIS SYSTEM. DURING MONITORING INFORMATION MAY BE EXAMINED, RECORDED, COPIED, AND USED FOR AUTHORIZED PURPOSES. ALL INFORMATION, INCLUDING PERSONAL INFORMATION, PLACED ON OR SENT OVER THIS SYSTEM MAY BE MONITORED. USE OF THIS DOD COMPUTER SYSTEM, AUTHORIZED OR UNAUTHORIZED, CONSTITUTES CONSENT TO MONITORING OF THIS SYSTEM. UNAUTHORIZED USE MAY SUBJECT YOU TO CRIMINAL PROSECUTION. EVIDENCE OF UNAUTHORIZED USE COLLECTED DURING MONITORING MAY BE USED FOR ADMINISTRATIVE, CRIMINAL OR OTHER ADVERSE ACTION. USE OF THIS SYSTEM CONSTITUTES CONSENT TO MONITORING FOR THESE PURPOSES.

Joint Enterprise DoD IIS Infrastructure
JEDI

Regular Desktop

Please enter your user name

Start Over Options Help

Warning Banner

Supports

- NIS
- NIS+
- LDAP/Sun ONE
- Local Files


Solaris 9 - JEDI User Environment




Solaris 9 - JEDI User Environment

JEDI 2.0 USES and Extends vendor-supplied PAM for

- **Authentication**
- **No Root Login**
- **Accept/Decline Banner**




Solaris 9 - JEDI User Environment




Solaris 9 - JEDI User Environment

Security Banner




Userpass

Print Status



Print Utility







DNS

NTP

Solaris 9 - JEDI/OE Security



- **Solaris 9 Public Design Review**

- JEDI 2.0 Requirements
- Support for Solaris 9
-  – Transition JEDI Tools to Role Based Access Control
- Transition JEDI Tools to Solaris Management Console
- Removing Dependency on JEDI Maps
- Secure Shell
- JASS Interface
- Pluggable Authentication Modules
- Flash Archive Support
- Optional SASF for Solaris 9
- Integration of ISS into JEDI 2.0 Baseline
- Additional Recommendations

- Transition JEDI Tools to Role Based Access Control
 - Features
 - Overview
 - Maintenance
 - Authorizations
 - Rights Profiles
 - Roles
 - Current JEDI TFM flow
 - New Process flow
 - Design Issues

Role Based Access Control (RBAC)

- **RBAC provides a fine-grained mechanism for managing the rights and authorizations of users and roles. Features of RBAC include:**
 - Available starting in Solaris 8
 - Authentication databases can be supported using NIS, NIS+, LDAP, or files
 - Administrators can create unlimited number of roles
 - User can belong to multiple roles
 - System supplied Application Programming Interfaces (API) which support C/C++, Java, and Shell Scripts
 - Integrated in with Sun's C2 audits
 - A vendor-supplied interface for maintaining Roles and Rights Profiles


RBAC - Overview

- **RBAC database files include**


- /etc/user_attr
- /etc/security/auth_attr
- /etc/security/prof_attr
- /etc/security/policy.conf
- /etc/security/exec_attr

- **These files allow a user to be associated with a specified authorization by**

- Assigning an authorization to a rights profile, the rights profile to a role, the role with a user (Preferred)
- Assigning an authorization to a rights profile, and the rights profile to the user
- Assigning an authorization directly to the user



- **RBAC uses 5 files to maintain authorizations and which users/roles have access to those authorizations. These files will be maintained as follows:**
 - **auth_attr**
 - Initially configured – During JEDI installation
 - Maintained – Not required
 - **prof_attr**
 - Initially configured – During JEDI installation
 - Maintained – Vendor-supplied interface
 - **user_attr**
 - Initially configured – During JEDI installation
 - Maintained – Vendor-supplied interface
 - **exec_attr**
 - No plans to configure or maintain for JEDI applications
 - **policy.conf**
 - No plans to configure or maintain for JEDI applications




- / **etc/security/auth_attr**
 - Defines “Authorization Strings”
 - Updated during the JEDI installation to include the default JEDI “Authorization Strings”
 - Does not require maintenance after the JEDI installation

• /
**etc/security/prof_a
ttr**


- Defines Rights Profiles
- Updated during the JEDI installation to include the default JEDI Rights Profiles
- There will be one Rights Profile entry for each unique JEDI Authorization String


– Maintained using 81



• /etc/user_attr


- Defines Roles and identify which user have access to those roles
- Updated during the JEDI installation to allow the user to install the Default JEDI roles or to create a custom Role
- Maintained using the Vendor-supplied Administrative Roles Interface





• Current Applications

- Use the `verify_tfm_user` function call
- Generates a warning message on failure
- Sanitizes a users environment
- Provides all-or-nothing access to an application



- **Modified Applications will**
 - Use the vendor-supplied API(s) to determine if a user has a specified authorization
 - Generates a warning message on failure
 - Have the ability to provide a more granular authorization check

RBAC - Design Issues

- **The current RBAC functionality provided by JEDI will sanitize a users environment, based on a configuration file, once a user has been validated. This is functionality that may not be re-created using Solaris's RBAC. With Solaris's RBAC, a role is nothing more than a specialized group. It is possible to control a role's environment by creating a profile for this group.**
- **With JEDI, a user can belong to one or more trusted roles, and have the ability to invoke more than one role at a time. With Solaris's RBAC, a user can belong to more than one role, but can only assume one role at a time.**
- **A profile/right may be assigned directly to a user. As a result, a user could make inadvertent mistakes by misuse of their privileges. This practice is discouraged by Sun.**
- **Since roles are implemented as a form of specialized user, all normal users who assume a specified role have access to that role's home directory, have access to the same files, and operate in the same environment.**
- **RBAC supports the locale variable. This allows the developer to create help files in different languages. Currently, we are only creating help files in English.**

- **Solaris 9 Public Design Review**

- JEDI 2.0 Requirements
- Support for Solaris 9
- Transition JEDI Tools to Role Based Access Control
- ➔ – Transition JEDI Tools to Solaris Management Console
- Removing Dependency on JEDI Maps
- Secure Shell
- JASS Interface
- Pluggable Authentication Modules
- Flash Archive Support
- Optional SASF for Solaris 9
- Integration of ISS into JEDI 2.0 Baseline
- Additional Recommendations

- Transition JEDI Tools to Solaris Management Console
 - Overview
 - Applications Requirements
 - Transitioned Applications
 - COTS Migration
 - Legacy Applications
 - Deprecated Applications

- **This is not Sun's Management Center**
- **SMC is a graphical user interface that provides access to Solaris System Administration tools**
- **SMC provides**
 - Support for Java 1.4 (for Solaris 9) and Java 1.3 (for Trusted Solaris 8)
 - Toolboxes to group administrative applications
 - Support for C2 Audits
 - A group of core services:
 - Authentication
 - Authorization
 - Logging
 - User Preferences
 - Persistence
 - Messaging
 - Application launch management
 - Files
 - LDAP
 - NIS
 - Management Scope which includes

SMC - Main Window Overview

Menu Bar

Location Line

Navigation Pane

Information Pane

Status Bar

Icon Bar

Results Pane

Management Tools: Solaris Management Console 2.1

Console Edit Action View Go Help

Toolbox: [http://crusher:898/toolboxes/smc.tbx#This Computer \(crusher\)/System Configuration/Users/User Accounts/](http://crusher:898/toolboxes/smc.tbx#This Computer (crusher)/System Configuration/Users/User Accounts/)

Navigation

- Management Tools
- This Computer (crusher)
 - System Status
 - System Configuration
 - Users**
 - User Accounts
 - User Templates
 - Rights
 - Administrative Roles
 - Groups
 - Mailing Lists
 - Printers

Name	Type	Description	User ID
root	Solaris	Super-User	0
daemon	Solaris		1
bin	Solaris		2
sys	Solaris		3
adm	Solaris	Admin	4
lp	Solaris	Line Printer Admin	71
uucp	Solaris	uucp Admin	5
nuucp	Solaris	uucp Admin	9

Information

User Accounts

Select an item.

Use this tool to add and manage user accounts.

Note: To manage user accounts, see [To Create a Name Service Domain](#).


If you selected User Accounts in the right pane, click **Action->Open** to see a list of existing users.

Context Help Console Events

16 User(s)

SMC Event tab

SMC - Main Window Overview Cont.





- **SMC allows a user to**
 - select which SMC display components will be shown
 - select the format of the view pane
 - sort the view pane by columns
 - use a filter to determine which object will be displayed in the view pane

- **Each JEDI application ported to the SMC framework will**
 - Have a tool descriptor file that contains
 - A large icon
 - A small icon
 - A description
 - A help file
 - Update the center pane of the Status Bar (Console Activity Indicator)
 - Update the Status Bar (Message Area)
 - Log to the SMC Event Log
 - Add appropriate information to the Menu Bar and Icon Bar
 - Support RBAC

- **JEDI TFM applications that will be transitioned to SMC include**
 - Alert News
 - Archive Utility
 - Assign Credentials (Host/User)
 - Assign Passwords
 - Boot Utility
 - Change File Information
 - Disk Space
 - Network Status
 - Session Maintenance
 - User Session Maintenance
 - User Account Information


- **Provides the ability to send Alerts/Sign on News to a workstation(s)**
 - Invoked from new menu/icon options
 - Same interface for both the Alert and Sign on News dialog
 - Workstations are selected from a list of icons displayed in the view pane





- **Allows a user to Archive Files / Directories**

- Invoked from the menu/icon bar
- Follows the JEDI V1.3 functionality




- **Allows a user to assign credentials for both host and users**

- Similar interface for both hosts and users
- Uses the View->Filter option to select
 - All Hosts
 - Hosts with credentials
 - Host without credentials

- **Allows an administrator to Assign/Expire a password(s)**

- Invoked from new menu/icon options
- User(s) are selected from a list of icons displayed in the view pane


Assigned Passwords will be grouped under User Account Maintenance





• Allows an administrator to Reboot/Halt a workstation(s)

- Invoked from new menu/icon options
- Host(s) are selected from a list of icons displayed in the view pane
- Common interface for both Halt and Reboot


Note: The “OS Boot Parameters” will only be displayed when a workstation is Rebooted




- **Allows a user to**
 - Change the owner / group of a file(s)
 - Change discretionary access of a file(s)
 - Follows the JEDI V1.3 functionality



- **Allows a user to**
 - Use the SMC navigation/view pane to drill down to a workstation
 - Use the property sheet for the specified workstation
 - Space Used
 - Free Space




- **Allows a user to**
 - Show network statistics
 - Follows the JEDI V1.3 functionality




- **Allows an administrator to control a user's log on environment**

- Supports menu/icon options to
 - Add
 - Delete
 - Modify




- **Allows a user to assign Sessions to a user/list of users**

- A list of users is displayed in the view pane
- Multiple users may be selected




- **Allows a user to view User Account Information**
 - Use the SMC navigation/view pane to drill down to a user
 - Use the property sheet to view information about the specified user
 - Use the SMC filter to limit the users displayed in the view pane



- **The following Trusted JEDI applications have been replaced with SMC Applications**
 - User Maintenance
 - Process Management
 - Printer Maintenance
 - Printer Status
 - Group Maintenance (no modifications made)
 - Host Maintenance (no modifications made)
- **Additional SMC Applications**
 - Dynamic Host Configuration Protocol


- **The vendor-supplied User Maintenance property sheet will be extended to include**

- Two new tabs for all Full Service Directory fields
- Support for Add / Modify / Delete commands
- Support drop down list for key Full Service Directory fields




SMC – User Account Maintenance Cont.

- **The vendor-supplied User Account Maintenance Add User Wizard will be extended to include**
 - Pane for all mandatory Full Service Directory fields
- **Note: A configuration file must be created to store all FSD field information (including update information)**




- **The vendor-supplied User Maintenance User Templates will be extended to include**

- Ability to set defaults for key Full Service Directory fields
- Support drop down list for key Full Service Directory fields




- **The vendor-supplied User Maintenance Menu/Icon bar will be extended to include**


- Menu/icon options for Enable Disable user accounts




- **The vendor-supplied Process Management will be extended to**
 - allow a user to send additional signals to a process



- **The vendor-supplied Admintool will be used to manage printers**
 - Launched from SMC




- **The vendor-supplied Printer Status utility will be used to manage print queues**
 - Launched from the SMC




- **Dynamic Host Configuration Protocol (DHCP)**
 - Moves management of the IP addresses away from the client systems and onto centralized servers
 - Eliminates the need for clients to store static network information
 - Supports storing the entire configuration for the booting of diskless clients

- **Dynamic Host Configuration Protocol (DHCP)**
 - Launched from SMC
 - Minimal configuration will be documented in the ICG
- **May causes problems with DII/COE**
- **Adds another test configuration**



- **Some Trusted JEDI applications will be marked as legacy applications**
 - RBAC-enabled
 - Launched from the SMC
 - CLASS
 - RDIST (May move to SMC port)
 - Launched as a user application (Not an SMC application)
 - Ping
 - Allocate/Deallocate



- **Allows a user to allocate / deallocate devices**
 - Graphical User Interface
 - Modified to support RBAC authorization checks
 - Launched from the background menu
 - Mirrors the Trusted Solaris implementation

- **The following Trusted JEDI applications will be removed from the baseline**
 - Privilege Maintenance
 - General Tools
 - Shell Tool
 - SPI Tool
 - Protocol Maintenance


- **Solaris 9 Public Design Review**

- JEDI 2.0 Requirements
- Support for Solaris 9
- Transition JEDI Tools to Role Based Access Control
- ➡ – Transition JEDI Tools to Solaris Management Console
- Removing Dependency on JEDI Maps
- Secure Shell
- JASS Interface
- Pluggable Authentication Modules
- Flash Archive Support
- Optional SASF for Solaris 9
- Integration of ISS into JEDI 2.0 Baseline
- Additional Recommendations

- **Removing Dependency on JEDI Maps**
 - Maps Removal
 - Naming service backup/restore utility

- **Support updating naming service tables directly**
 - Transitioning to vendor-supplied
 - Group Maintenance
 - Host Maintenance
 - User Maintenance
- **Support Full Service Directory fields**
 - Extending User Maintenance
 - Add User Wizard
 - User Templates
- **Support Add / Remove / Modify commands**
 - Extending User Maintenance
- **Support Map Defaults**
 - User Maintenance's "User Templates"

Maps - Backup Utility



- **Retain the capability to backup and restore naming service data**

- Provide a naming service backup/restore utility
 - Modify SMC to manually call this utility
 - Configure Solaris Cron Utility to automatically call this utility

- **Solaris 9 Public Design Review**

- JEDI 2.0 Requirements
- Support for Solaris 9
- Transition JEDI Tools to Role Based Access Control
- Transition JEDI Tools to Solaris Management Console
- – Removing Dependency on JEDI Maps
- Secure Shell
- JASS Interface
- Pluggable Authentication Modules
- Flash Archive Support
- Optional SASF for Solaris 9
- Integration of ISS into JEDI 2.0 Baseline
- Additional Recommendations

- **Secure Shell (SSH)**

- Secure Shell - Solaris 9
- Secure Shell - Protocols 1 and 2
- Secure Shell - Affects on RDIST and the Accept/Decline banner
- Secure Shell - /etc/ssh/ssh_config
- Secure Shell - Configuration GUI for SSH
- Secure Shell - Support for Solaris 8

- **Secure Shell is provided with Solaris 9**
- **ssh (Secure Shell) is a program for logging into a remote machine and for executing commands on a remote machine**
 - Intended to replace rlogin and rsh
 - Provide secure encrypted communications between two untrusted hosts over an insecure network
- **ssh connects and logs into the specified hostname**
 - User must prove his or her identity to the remote machine
 - Two protocol methods
 - SSH Protocol 1
 - SSH Protocol 2
 - All communication with the remote command or shell is automatically encrypted

- **SSH Protocol 1**

- RSA authentication protocol
- Private key in \$HOME/.ssh/identity
- Public key in \$HOME/.ssh/identity.pub
- Keys reside in the user's home directory

- **SSH Protocol 2**

- Public Key method similar to RSA in Protocol 1
 - DSA algorithm instead of patented RSA algorithm
- Private key in \$HOME/.ssh/id_dsa
- Public key in \$HOME/.ssh/authorized_keys
- Keys reside in the user's home directory
- Strong mechanism for ensuring integrity of the connection
 - Traffic encrypted using 3DES, Blowfish, CAST128 or Arcfour
 - Integrity ensured with hmac-sha1 or hmac-md5

- **RDIST and Secure Shell**

- Previous versions of RDIST utilized rsh for communications between hosts
- RDIST for the Solaris 9 effort will utilize ssh
 - Changes will be made to RDIST for ssh
 - Legacy support for RDIST will be managed through the configuration of ssh
 - **UseRsh configuration parameter on a per legacy host basis will allow RDIST to communication using rsh**
 - **UseRsh parameter is stored in the ssh_config file**
 - **UseRsh parameter will be managed by the SSH_Config GUI**

- **Accept/Decline banner and Secure Shell**

- Ssh for Solaris 9 supports PAM
- Support for the Accept/Decline banner using PAM and the UseLogin SSH parameter stored in the ssh_config file
- UseLogin parameter will be managed by the SSH-Config GUI


- **/etc/ssh/ssh_config**

- Contains the settings used by the Secure Shell software
- Creating a GUI for managing this file
- GUI will be a SMC Component


- **ssh_config GUI**


- Help panel describing the options displayed
- Reads the /etc/ssh/ssh_config file
- If file is “empty”, then the defaults will be shown in the GUI for the JEDI configuration
- Cancel forgets the changes made to the file
- OK saves the changes to the file

Secure Shell - Configuration GUI for SSH




Secure Shell - Configuration GUI for SSH (cont)





The image shows a Windows-style dialog box titled "SSH Property for Speedy". It has a standard title bar with minimize, maximize, and close buttons. On the left is a "Help" pane with the text "Set the Options required for each host". The main area has three tabs: "Typical", "Advanced", and "More Advanced". The "Advanced" tab is selected. It contains several configuration options, each with a label and a corresponding input field or spinner. The options are: "ConnectionAttempts" (spinner set to 5), "CompressionLevel" (spinner set to 9), "EscapeChar" (text field with "~"), "HostName" (empty text field), "LocalForward" (empty text field), "NumberOfPasswordPrompts" (text field with 3), "Port" (text field with 22), "Protocol" (spinner set to 2), "RemoteForward" (empty text field), and "User" (empty text field). At the bottom right are "Ok" and "Cancel" buttons.

Property	Value
ConnectionAttempts	5
CompressionLevel	9
EscapeChar	~
HostName	
LocalForward	
NumberOfPasswordPrompts	3
Port	22
Protocol	2
RemoteForward	
User	



- **OpenSSH for Solaris 8**

- Version 3.7.1p2
- Software in Solaris pkgadd format
 - Download packages from sunfreeware.com
 - Security Fixes
 - Download new version from sunfreeware.com
 - Uninstall package(s) and Install in version(s)
- Additional support packages
 - Openssl 0.9.7c
 - Zlib 1.1.4
 - Libgcc 3.3
 - Tcp Wrappers 7.6
 - Solaris 8 patch 112438-02 for /dev/random device
- Provide needed packages on JEDI cdrom
- Provide installation documentation


- **Solaris 9 Public Design Review**

- JEDI 2.0 Requirements
- Support for Solaris 9
- Transition JEDI Tools to Role Based Access Control
- Transition JEDI Tools to Solaris Management Console
- – Removing Dependency on JEDI Maps
- Secure Shell
- JASS Interface
- Pluggable Authentication Modules
- Flash Archive Support
- Optional SASF for Solaris 9
- Integration of ISS into JEDI 2.0 Baseline
- Additional Recommendations


- **JASS Interface**
 - JASS Interface – JEDI/OE Security
 - JASS Interface – GUI

- **JEDI 2.0 will use the JASS software as a platform for implementing**
 - Security guidelines
 - Templates
 - Best practices
 - Minimizing the Solaris 9 OE
 - Tightening network settings
- **JEDI 2.0 will make reasonable modifications to network parameters and protocols**
- **These settings will not compromise the functionality of JEDI 2.0 or site applications**

- **JEDI 2.0 will install a JASS configuration file to implement the following**
 - Harden the File System
 - Ensure the latest Solaris OE is installed
 - Ensure the latest patches are installed
 - Ensure that Console Security is set correctly (EEPROM settings)
 - Ensure that Keyboard Abort is disabled
 - Ensure that Mount Options read-only, nosuid
 - In accordance with site policy
 - Ensure that Volume Management is Disabled
 - In accordance with site policy



- **JEDI 2.0 will provide a GUI front end for configuring workstation and network settings**
- **Security Settings will be broken down into two virtual groups**
 - Network settings
 - OS Settings



Network Settings

Help

Select an item on the right to see help for that item -->

Misc Security Settings ARP / IP Settings TCP Settings UDP Settings

Connection Request Max q0 4096

Connection Request Max q 1024

Smallest Anonymous Port 32768

Largest Anonymous Port 655389

Smallest Non-Privileged Port 1024

Extra Privileged Ports 4096

☒ Rev Source Routes

Ok Cancel

Network Settings

Help

Select an item on the right to see help for that item -->

Misc Security Settings | ARP / IP Settings | TCP Settings | UDP Settings

Smallest Anonymouns Port 32768

Largest Anonymous Port 65535

Smallest Non-Privileged Port 32768

Extra Privileged Ports 65535

Ok Cancel


- **Solaris 9 Public Design Review**

- JEDI 2.0 Requirements
- Support for Solaris 9
- Transition JEDI Tools to Role Based Access Control
- Transition JEDI Tools to Solaris Management Console
- Removing Dependency on JEDI Maps
- – Secure Shell
- JASS Interface
- Pluggable Authentication Modules
- Flash Archive Support
- Optional SASF for Solaris 9
- Integration of ISS into JEDI 2.0 Baseline
- Additional Recommendations


- **Pluggable Authentication Modules**
 - PAM – Incorporate New Native PAM
 - PAM – Login Functional Flow
 - PAM – Authentication Modules
 - PAM – Account Modules
 - PAM – Support for Password History
 - PAM – Password History Flow
 - PAM – Password History Updates – NIS
 - PAM – Password History Updates – NIS+/LDAP

- In JEDI 2.0, PAM Modules will be implemented for


- PAM Authentication Modules
- PAM Account Modules
- PAM Password History



PAM - Login Functional Flow




- The user is prompted for the password during the login process
- The password is passed to the PAM Modules for authentication and verification
- If the password is correct and passes verification, the user is logged in



- **JEDI 2.0 will implement, as part of the Authentication Process, Modules for**
 - **Unix Authentication**
 - **User Lockout**
- **Under Solaris 9, The PAM Unix Modules are broken down into six modules**
 - **Pam_authtok_get**
 - **Pam_authtok_check**
 - **Pam_authtok_store**
 - **Pam_unix_auth**
 - **Pam_dhkeys**
 - **Pam_passwd_auth**

- **Modules will return standard PAM return codes to indicate success or failure of the module**
 - PAM_AUTH_ERR
 - PAM_AUTHTOK_EXPIRED
 - PAM_SUCCESS
 - PAM_FAILURE
 - PAM_USER_UNKNOWN
- **The return codes are interpreted by the login process**
 - Dtlogin
 - FTP
 - Telnet

PAM - Account Modules



- **JEDI 2.0 will implement, as part of the Account Verification Process, Modules for**
 - No Root Login
 - Password Aging
 - Accept Decline Banner
 - Password Rules

- **Password Rules will be implemented as a PAM Module**
 - Solaris 9's PAM Password Module will be used to implement the following rules
 - Each password must have PASSLENGTH characters, where PASSLENGTH is defined in /etc/default/passwd
 - Each password must contain at least two alphabetic characters and at least one numeric or special character
 - Each password must differ from the user's login *name* and any reverse or circular shift of that login *name*
 - New passwords must differ from the old by at least three characters

- **The following rules will be implemented in PAM and will remain configurable**
 - Password must be at least 8 characters long
 - No repeating characters allowed as part of password
 - Password must be mixed case
 - Password must contain a special character
 - Login name not allowed as password
 - Reversed login name not allowed as password
 - First name not allowed as password
 - Reversed first name not allowed as password
 - Last name not allowed as password
 - Reversed last name not allowed as password
 - Office not allowed as password
 - Reversed office not allowed as password
 - Phone number not allowed as password
 - Reversed phone number not allowed as password


- **The following rules will be implemented in PAM and will remain configurable (continued)**
 - Initials not allowed as password
 - New password cannot be the same as previous password
 - User ID is not allowed as password or as part of password
 - Circular shift of username not allowed as password
 - Host name not allowed as password
 - Reversed host name not allowed as password
 - Domain name not allowed as password
 - Reversed domain name not allowed as password
 - Domained host name not allowed as password
 - Dictionary entries not allowed as password
 - Leading dictionary words not allowed as password
 - Trailing dictionary words not allowed as password
 - Password cannot have eight of the same characters

- **JEDI 2.0 will use the Password History Object in LDAP**
 - The LDAP PasswordHistory has the following structure:
 - Binary, multiple values
 - Updated using the ldapmodify command
- **A password history table will be implemented in NIS+, NIS, and local files with the following format**
 - User:passwd1,passwd2, ..., passwdn
 - Readable and writeable only by root
- **Created during the JEDI 2.0 Installation**
- **Invisible to the user**

PAM - Support for Password History

- **At installation time, the following attributes will be set in LDAP**
 - passwordHistory set to *on*
 - passwordInHistory set to *n*
 - Where *n* is the number of passwords to keep in the history
 - *N* defaults to 6
- **Two new variables will be added to the password.data**
 - PASSWORD_HISTORY
 - PASSWORD_IN_HISTORY
- **These variables will be set to the same values as collected in the installation software**

PAM - Password History Flow



- **Password History checking will be implemented as a rule in the passwd.data file**
- **Can be performed at any point in the password checking process**
- **Configurable by a trusted user**
- **Exceptions**
 - Password will not be in the history if the list is blank

PASSORD_HISTORY=Yes

PASSORD_IN_HISTORY=6

Encrypted_New_Password


Last Used Password



6th Last Used Password



- Passwords are stored as encrypted values
- Userpass will read the **PASSORD_HISTORY** variable
 - If set to Yes, Userpass will update the password history list
- Passwords are moved down the list
 - The last used password is moved to the number two slot
 - The 2nd last used password is moved to the number 3 slot, and so on
 - The nth password is discarded




- **NIS**

- Userpass updates the passwd.history file
- Make is executed updating the passwd.history table



- **NIS+**

- Userpass updates the passwd.history.org_dir table
 - Nisaddent commands



- **LDAP**

- Userpass updates the PasswordHistory Object in LDAP
 - Ldapmodify commands

- **Solaris 9 Public Design Review**

- Requirements
- Support for Solaris 9
- Transition JEDI Tools to Role Based Access Control
- Transition JEDI Tools to Solaris Management Console
- Removing Dependency on JEDI Maps
- Secure Shell
- – JASS Interface
- Pluggable Authentication Modules
- Flash Archive Support
- Optional SASF for Solaris 9
- Integration of ISS into JEDI 2.0 Baseline
- Additional Recommendations

- **Flash Archive Support**
 - Flash Archive Support – Method
 - Flash Archive Support – Baseline

- **How will Flash archive be supported**
 - Jumpstart servers are created using the same methods for both normal jumpstart and flash archive support
 - Existing “Jumpstart Supplement” will be modified
 - **Section 2.1 “Solaris Jumpstart Overview” will be modified to introduce the concept of a “Flash Archive”**
 - **A new “Creating a Flash Archive” section will be added**


- **Install and configure the system**
- **Create a Flash Archive**
- **Move the Archive to the Jumpstart Server**
- **Edit the rules file to use the archive**
- **Jumpstart the client system**
- **Test the system to determine if any of the COTS/GOTS software require an after-the-flash configuration**

- **Flash Archive Directory Added**
 - Existing jumpstart directory structure will be modified to introduce a directory where newly created Flash Archives can be stored
- **Scripts**
 - Flash.begin and Flash.finish example scripts will be added
- **Rules**
 - Rules file will have an example rule added in support of a flash installation

- **Solaris 9 Public Design Review**

- Requirements
- Support for Solaris 9
- Transition JEDI Tools to Role Based Access Control
- Transition JEDI Tools to Solaris Management Console
- Removing Dependency on JEDI Maps
- Secure Shell
- JASS Interface
- – Pluggable Authentication Modules
- Flash Archive Support
- Optional SASF for Solaris 9
- Integration of ISS into JEDI 2.0 Baseline
- Additional Recommendations

- **Optional SASF for Solaris 9**
 - SASF – DII COE/JEDI Architecture
 - SASF – Modifications to DII COE
 - SASF – DII COE Installation Paths



- **No runtime DII COE changes discovered to date**
- **Primary effort is dedicating to installing, verification, and testing**

- **DII COE Kernel Modifications**

- VerifySolarisVersion
 - Modify case statement to include Solaris 9 as an acceptable OS Version
- CheckForFirstPatches
 - Modify case statement to include required patches for Solaris 9

- **ICSF Segment Modifications**

- Process
 - Unbundle
 - Modify PostInstall for Solaris 9 installation
 - VerifySeg
 - MakeSeg (rebundle)

- **Issues**

- Examining options for grouping the target segments into sets

- **ICSF Segments**
 - Java Platform 2
 - Solaris Patch Update
 - JMTK Utilities Segment
 - JMTK SDBM
 - JMTK Analysis
 - Integrated Foundation Library
 - JMTK - Visualization
 - JMTK-V Map Data
 - Application Framework
 - Tactical Management System
 - TMS-Visualization
 - Universal Comms Processor
 - ICSF C4I

- **Fresh Install**

- Install Solaris 9
- Install JEDI 2.0
- Install Modified DII COE with Patch 9 (or latest available patch)
- Install Modified ICSF Segments

- **Upgrade**


- Existing System
 - Solaris 8, DII COE 4.2.0.5, JEDI 1.3, ICSF Segments
- Patch DII COE to Patch 9
- Upgrade Solaris 8→9
- Upgrade JEDI 1.3→2.0

- **Solaris 9 Public Design Review**

- Requirements
- Support for Solaris 9
- Transition JEDI Tools to Role Based Access Control
- Transition JEDI Tools to Solaris Management Console
- Removing Dependency on JEDI Maps
- Secure Shell
- JASS Interface
- Pluggable Authentication Modules
- – Flash Archive Support
- Optional SASF for Solaris 9
- Integration of ISS into JEDI 2.0 Baseline
- Additional Recommendations


- **Integration of ISS into JEDI 2.0 Baseline**
 - ISS – Changes to Installation
 - ISS – Data Flow

ISS - Changes to Installation



ISS Server
(Windows based)

ISS System Scanner agent
(Solaris System)



- **Solaris 9 Public Design Review**

- Requirements
- Support for Solaris 9
- Transition JEDI Tools to Role Based Access Control
- Transition JEDI Tools to Solaris Management Console
- Removing Dependency on JEDI Maps
- Secure Shell
- Pluggable Authentication Modules
- Flash Archive Support
- – Optional SASF for Solaris 9
- Integration of ISS into JEDI 2.0 Baseline
- Additional Recommendations

- **Remote Desktop**
- **Update Xautolock**